

# SDV Field Bulletin - 8

Product changes, updates, and communications

October 27, 2004



## Dura/Liner masonry relining system for all-fuel burning appliances

Dura/Liner is Simpson Dura-Vent's premium high temperature masonry relining system. The double-wall, factory insulated, relining system is available in 24", 36", and 48" lengths of factory ovalized round, oval and oval-to-round configurations. Dura/Liner ensures a correctly sized and insulated flue to maintain proper performance and efficiency.

Dura/Liner relining is offered with a 25 year warranty from the date of installation. Dura/Liner can assist in restoring deteriorating chimneys when combined with DuraTech or Dura/Plus Chimney. When a masonry chimney is damaged or fallen down, it can be replaced with a safe factory-built chimney.

Dura/Liner, when used with a Transition Anchor Plate and in combination with DuraTech or Dura/Plus Chimney, replaces the damaged masonry chimney with a safe, efficient, and economical chimney that is UL and ULC Listed and tested.

Here is the current Dura/Liner product offerings. Dura/Liner price lists will be available, and mailed, the first week on November.

<b>Dura/Liner</b>	<b>6"</b>	<b>8"</b>
12" Length Round Single-Wall Pipe	4012	4212
12" Length Round Rigid Pipe	4612	4812
24" Length Round Single-Wall Pipe	4024	4224
24" Length Round Rigid Pipe	4624	4824
36" Length Round Single-Wall Pipe	4036	4236
36" Length Round Rigid Pipe	4636	4836
48" Length Round Single-Wall Pipe	4048	4248
48" Length Round Rigid Pipe	4648	4848
12" Length Oval Rigid Pipe	4612-OP	4812-OP
24" Length Oval Rigid Pipe	4624-OP	4824-OP
36" Length Oval Rigid Pipe	4636-OP	4836-OP
48" Length Oval Rigid Pipe	4648-OP	4848-OP
36" Length Round-to-Round Flex	4636-F	4836-F
60" Length Round-to-Round Flex	4660-F	4860-F

<b>Dura/Liner <i>continued</i></b>	<b>6"</b>	<b>8"</b>
36" Length Oval-to-Oval Flex	4636-OF	4836-OF
60" Length Oval-to-Oval Flex	4660-OF	4860-OF
36" Length Oval-to-Round Flex	4636-OR	4836-OR
60" Length Oval-to-Round Flex	4660-OR	4860-OR
14" Length Round-to-Oval Flex	4614-RO	4814-RO
Masonry Thimble w/ Slip Connector	4643	4843
Wall Pass Through	4644	4844
Adjustable Sleeve	4666	4866
Round Tee w/Round Branch w/cap	4667	4867
Oval Tee w/Round Branch w/cap	4667-O	4867-O
DuraFlex SS Tee	7143	7145
Transition Anchor Plate 14" x 17" - D/P	9040A	9240A
Transition Anchor Plate 17" x 17" - D/P	9040B	9240B
Transition Anchor Plate 13" x 21" - D/P	9040C	9240C
Transition Anchor Plate 17" x 21" - D/P	9040D	9240D
Transition Anchor Plate 14" x 17" - DT	9440A	9640A
Transition Anchor Plate 17" x 17" - DT	9440B	9640B
Transition Anchor Plate 13" x 21" - DT	9440C	9640C
Transition Anchor Plate 17" x 21" - DT	9440D	9640D
Slip Connector and Hanger	4671	4871
Spacer (Round)	4668	4868
Spacer (Oval)	4668-O	4868-O
30° Stove Connector (Round-Round)	4681	4881
30° Stove Connector (Round-Oval)	4681-RO	4881-RO
30° Stove Connector (Oval-Round)	4681-O	4881-O
30° Stainless Steel Elbow	4630	4830
45° Stainless Steel Elbow	4645	4845
Flat Stove Connector (Round)	4680	4880
Flat Stove Connector (Oval)	4680-O	4880-O
Extend-A-Cap Kit (Round) 13" x 13"	4685	4885
Extend-A-Cap Kit (Round) 13" x 18"	4686	4886
Extend-A-Cap Kit (Oval) 10" x 22"	4687-O	4885-O
Extend-A-Cap Kit (Oval) 13" x 20"	4688-O	4886-O
Two-Ply Insulation Sleeve (60")	7102-ZC	7104-ZC
Single-Wall End Ring Adapter	4000	4200
Insulation Clamp (Round or Oval)	4910	4910