

FasNSeal Single and Double Wall Wye

The FasNSeal single and double wall wye can be used in place of any M&G DuraVent tees, with the difference being that the branch is at a 45° angle instead of 90°. The wye can be used as a manifold connection to gang multiple boilers into a common vent.



Features

- 45° branch angle
- Used as a manifold connection to gang multiple boilers into a common vent
- Built-in manifold locking band
- Ease of installation

Materials:

FasNSeal
AL29-4C

FasNSeal W2
AL29-4C stainless steel inner wall,
stainless steel outer wall

| Single | Stock # | Order # |
|--------|---------|---------|
| 6" | 303163 | FSWYE06 |
| 7" | 303164 | FSWYE07 |
| 8" | 303165 | FSWYE08 |
| 9" | 303166 | FSWYE09 |
| 10" | 303167 | FSWYE10 |
| 12" | 303168 | FSWYE12 |
| 14" | 303169 | FSWYE14 |

| Double | Stock # | Order # |
|--------|---------|----------|
| 6" | 103163 | W2-WYE06 |
| 7" | 103164 | W2-WYE07 |
| 8" | 103165 | W2-WYE08 |
| 9" | 103166 | W2-WYE09 |
| 10" | 103167 | W2-WYE10 |
| 12" | 103168 | W2-WYE12 |
| 14" | 103169 | W2-WYE14 |